



Americrete, Inc.
41730 Reagan Way
Murrieta, Ca 92562
Toll Free (800) 775-8880
Technical Help (800) 775-8880

Material Safety Data Sheet A-900

Emergency Assistance

For Chemical Emergency Spill, Leak, Fire or Exposure call 24 hours a day: **CHEMTREC** (800) 424-9300. Outside U.S. call (703) 527-3887. Collect calls accepted.

SECTION I PRODUCT IDENTIFICATION

Product Name: Gray-Waterproofing Base Coat A-900
Product Class: Dry Co-Polymer Emulsion mixed with different size sand and Portland cement.

HMIS Rating: Health 1 Fire 0 Reactivity 0
0=Least, 1=Slight, 2=Moderate, 3=High, 4=Extreme

SECTION II PHYSICAL DATA

Appearance: Cement Gray
Odor Characteristic: Ester/acetic Odor
Specific Gravity: 3.10
Vapor Density: N/A
Solubility in Water: Dilutable
Evaporation Rate: N/A

SECTION III FIRE AND EXPLOSION HAZARD DATA

Flammability Class: N/A«flammabilityclass»
Flash Point: N/A
LEL: N/A
Extinguishing Media: Water, CO2 or Dry Chemical
Unusual Fire and Explosive Procedures: Wear Self-contained breathing apparatus

SECTION IV HEALTH HAZARD DATA

Permissible Exposure Level: The ACGIH TLV and OSHA PEL for vinyl acetate are both set at 100ppm for an 8 hour TWA and at 20 ppm for the STEL
Effects of Overexposure:

- Inhalation: Headache, nausea, irritation of the nose, throat and lungs, vomiting
- Skin Contact: May cause slight irritation

Chemical Control Laws: All components of this product are listed or are excluded release reporting under section 33 Vinyl acetate (108-05-04).

State Right-to-Know Laws: Any material listed as “not hazardous” in the CAS column of the ingredient information section of this MSDS is trade secret under the provisions of the Pennsylvania worker and community right-to-know act.

California Prop 65: This product contains trace amounts of a component or components known to the state of California to cause cancer: Acrylamide (79-06-1) <0.1%, and Acetaldehyde (75-07-0) <0.1%