



Product Description

Graff Shield products are non-hazardous, water base anti-graffiti coatings that deter, lift and eliminate graffiti from surfaces. These water base products were designed to: deter graffiti markings, lift graffiti from surfaces that have been protected and eliminate graffiti markings.

Package Size

1 gallon containers, 5 gallon buckets and 55 gallon drums. GS-300 Graffiti Eliminator also comes in a 22 ounce spray bottle.

Surface Preparation

Graff Shield products can be applied to any painted or unpainted interior or exterior surface. The surface should be clean and free of dust, grease, etc. Do not apply GS-100 to deteriorating substrates. Do not apply over surfaces that have been acid washed and not properly neutralized with soda ash and/or baking soda.

Painted Surfaces

Do not apply Graff Shield products over fresh paint. Allow the paint to cure properly as these products could discolor paint surfaces. Do a test before installation.

Masonry/Concrete Surfaces

Concrete must be cured for one week before applying Graff Shield products to the surface. Contact your Americrete representative for more information.

Surface and Material Testing

Every surface should be tested to determine compatibility of the A-GS1000 system.

Advantages and Uses

Advantages

- Chemical Resistant
- Water Clean-Up
- Non-Hazardous
- Water Base

- Tough
- No Smell
- Environmentally Friendly
- Non toxic
- U.V. Resistant

Uses

- Block
- Tile
- Masonry
- Concrete
- Brick
- Metal
- Wood
- Stucco
- Rubber

Application Equipment

Best if applied by an airless spray equipment set at normal painting pressure. Use a tip size of .011 to .013. May be applied by roller, clean soft brush, Hudson Sprayers, etc.

Application Procedure

This is a two-step application process. First, by starting at the bottom and working your way to the top, apply GS-100 Graffiti Deterrent onto the substrate, saturate the surface and allow to dry. Once dry, apply a coat of GS-200 Graffiti Lift to the surface. A 2nd coat of GS-200 Graffiti Lift can be applied to heavily tagged areas for easier removal. Note: For extremely porous surfaces apply two coats of GS-100 Graffiti Deterrent and two coats of GS-200 Graffiti Lift for best results.

Products Needed for 300 Square Feet

- 1 Gallon GS-100 Graffiti Deterrent
- 1 Gallon GS-200 Graffiti Lift
- Optional:
- 1 Gallon GS-300 Graffiti Eliminator

Graffiti Removal

Simply use a 3000 PSI power washer with a 15 degree tip with hot or cold water. If necessary, spray GS-300 Graffiti Eliminator onto the surface. Let stand for approximately 30 minutes. This will help to clean tough markings.

Drying Time

Surface: 1 hour. Re-coat when surface is dry to the touch. Full chemical cure within 36-48 hours. CAUTION: Do not attempt to remove graffiti while surface is curing.

Clean-Up

Simply rinse with water.

Storage

Store in a protected area between 45 degrees and 90 degrees F. Protect from freezing.

Shelf Life

One year in unopened containers.

Coverage

150–250 sq. ft. per gallon on rough or porous surfaces. 300-400 sq. ft. per gallon on smooth dense surfaces.

General Precautions

Graff Shield products are non-flammable. If interior surfaces are being coated, make sure the area is well ventilated. Wear protective eyewear. Avoid runs. If Graff Shield products are exposed to rain before curing process is complete you may need to reapply product for proper performance.

Graffiti Removal: Always Remove Graffiti Defacement Promptly!

No one solvent will remove all graffiti. Try water first. If water does not remove graffiti, use GS-300 Graffiti Eliminator. Be sure the surface is completely dry before applying GS-300. Allow to stand 30 minutes before removing.

Mildew Areas:

Note: Do not apply GS-1000 System over mildew. To remove mildew, power wash area. Make need to clean with TSP or other cleaner before proceeding with GS-1000 System.

CAUTION

Do not take internally. Close container after each use. Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

Product Warranty:**Americrete will uphold Graff Shield Warranty as follows:**

Graff Shield International, Inc. warranties that this product is blended to the highest quality. This warranty is only for replacement of material and will only if the material that was applied was documented by either a Graff Shield International representative and/or by an agent or certified applicator of Graff Shield products. This can also be done by video taping the installation.

Graff Shield must be applied by using GS-100 Graffiti Deterrent in conjunction with GS-200 Graffiti Lift at a rate of 300 square feet per gallon. If graffiti is remove, an additional coat of GS-200 Graffiti Lift must be re-applied for this warranty be valid. To remove graffiti markings, apply GS-300 Graffiti Eliminator to the surface as

described on the product information page. The use of any other product other than Graff Shield's GS-300 Graffiti Eliminator will void this warranty.

Note: Americrete products are to be applied only when surface temperatures are at 55 degrees or higher. Do not apply when rain or other precipitation is expected within 24 hours.